



Ambulance Cleaning Protocol

Ambulance Compartment:

1. Utilise Personal Protective Equipment (PPE) as required.
2. Remove all equipment and consumables from ambulance.
3. Carefully inspect floor, side door tracks, clamp tracks and any other at risk areas for blood spillages and sharps. Any hazards identified must be dealt with according to the Infection Control Policy. An incident report form must be completed if hazardous sharps are found.
4. Vacuum ambulance floor (if necessary).
5. Apply G clean to exterior door frames.
6. Steam clean difficult to clean areas (eg. gaps between fixtures) and exterior door frames.
7. Steam clean floor edges.
8. Steam clean ambulance interior surfaces
9. Work methodically to wipe down any other surfaces with detergent wipes.
10. Use the floor scrubber machine with appropriate pad to maintain the ambulance floor. Use wet vac to remove all water.
11. Mop floor using Chlor Clean solution and blue mop.

Ambulance Cab:

1. Vacuum front floor and door pockets.
2. Clean steering wheel, gear stick and radio microphone and other surfaces with disposable detergent wipes.

Exterior:

1. Clean exterior using pressure washer and traffic film remover.

Monitoring:

1. Note completed clean in vehicle log book.
2. Ensure clean is logged on the fleet computer system.
3. The Fleet Engineer must be informed if any vehicle arrives in an unacceptable state.